


## VACUFLEX® K1H-TPR

Light weight and highly flexible TPR hose

|                     |   |
|---------------------|---|
| <b>Applications</b> | automotive engineering, engine construction, filter systems, compressors, ventilation   |
| <b>Structure</b>    | TPR, black, opaque, steel wire / spring steel wire / coated / PP  |
| <b>Temperature</b>  | -40°C up to 135°C, short term up to 150°C   |
| <b>Properties</b>   | light weight, very good flexibility, good temperature resistance, good chemical resistance, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof, rot proof |



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Length (m) | Article Number    |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|-------------------|---------------|------------|-------------------|
| 19                  | 24,60               | 0,65                | 19                  | 1,00                          | 0,60              | 0,10200       | 30         | 1-1906-019-00     |
| 25                  | 30,60               | 0,65                | 25                  | 0,90                          | 0,55              | 0,13500       | 30         | 1-1906-025-00/998 |
| 32                  | 37,60               | 0,65                | 32                  | 0,90                          | 0,55              | 0,16900       | 30         | 1-1906-032-00/998 |
| 35                  | 40,60               | 0,65                | 35                  | 0,90                          | 0,55              | 0,19000       | 30         | 1-1906-035-00/998 |
| 38                  | 43,60               | 0,65                | 38                  | 0,90                          | 0,55              | 0,20600       | 30         | 1-1906-038-00/998 |
| 40                  | 45,60               | 0,65                | 40                  | 0,90                          | 0,55              | 0,21700       | 30         | 1-1906-040-00/998 |
| 45                  | 50,60               | 0,65                | 45                  | 0,90                          | 0,55              | 0,24500       | 30         | 1-1906-045-00/998 |
| 50                  | 56,00               | 0,65                | 50                  | 0,70                          | 0,55              | 0,26700       | 30         | 1-1906-050-00/998 |
| 60                  | 66,00               | 0,65                | 60                  | 0,70                          | 0,50              | 0,33900       | 30         | 1-1906-060-00/998 |
| 70                  | 76,40               | 0,65                | 70                  | 0,70                          | 0,50              | 0,42400       | 30         | 1-1906-070-00/998 |
| 75                  | 81,40               | 0,65                | 75                  | 0,70                          | 0,50              | 0,45500       | 30         | 1-1906-075-00     |
| 80                  | 87,00               | 0,65                | 80                  | 0,70                          | 0,50              | 0,61900       | 30         | 1-1906-080-00/998 |
| 90                  | 97,00               | 0,65                | 90                  | 0,70                          | 0,50              | 0,71200       | 30         | 1-1906-090-00/998 |
| 100                 | 107,00              | 0,65                | 100                 | 0,50                          | 0,45              | 0,79300       | 30         | 1-1906-100-00/999 |
| 110                 | 117,00              | 0,65                | 130                 | 0,50                          | 0,45              | 0,87200       | 30         | 1-1906-110-00/998 |
| 120                 | 127,00              | 0,65                | 150                 | 0,50                          | 0,45              | 0,95200       | 30         | 1-1906-120-00     |
| 125                 | 132,00              | 0,65                | 175                 | 0,50                          | 0,45              | 0,99200       | 30         | 1-1906-125-00     |
| 130                 | 138,00              | 0,65                | 180                 | 0,40                          | 0,20              | 1,03200       | 30         | 1-1906-130-00     |
| 140                 | 148,00              | 0,65                | 185                 | 0,40                          | 0,20              | 1,11200       | 30         | 1-1906-140-00     |
| 160                 | 168,00              | 0,65                | 195                 | 0,40                          | 0,20              | 1,26900       | 30         | 1-1906-160-00/998 |
| 160                 | 168,00              | 0,65                | 195                 | 0,40                          | 0,20              | 1,26900       | 30         | 1-1906-160-00/999 |
| 170                 | 178,00              | 0,65                | 200                 | 0,40                          | 0,20              | 1,34900       | 30         | 1-1906-170-00     |

| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|-------------------|---------------|------------|----------------|
| 200                 | 208,00              | 0,65                | 250                 | 0,20                          | 0,15              | 1,58800       | 30         | 1-1906-200-00  |
| 255                 | 263,00              | 0,65                | 335                 | 0,20                          | 0,15              | 2,03400       | 15         | 1-1906-255-00  |
| 300                 | 308,00              | 0,65                | 420                 | 0,10                          | 0,10              | 2,39300       | 15         | 1-1906-300-00  |
| 400                 | 408,00              | 0,65                | 520                 | 0,10                          | 0,10              | 4,11400       | 15         | 1-1906-400-00  |